



High Performance Procedure Mask



KEY FEATURES

The 3 layer design provides BFE and PFE > 98%
 One size fits all (17.5 x 9.5cm)
 Adjustable nose clip significantly reduces air penetration
 Ultrasonically welded earloops stay firmly attached
 Tested for quality in the United States

MATERIAL COMPOSITION

Outer and inner layers – spunbond nonwoven polypropylene
 Filter – meltblown nonwoven polypropylene
 Straps – polyester elastic cord
 Nose clip – metal wire with plastic covering
 This mask contains no components made from natural rubber latex
 Approximate weight of product: 3.0 grams / 0.10 oz

INTENDED USAGE

The mask is intended to be worn by healthcare personnel and covers the user's nose and mouth
 The mask provides a physical barrier to block pollutants from nose and mouth and to reduce risks of spreading viruses and breathing in airborne particles
 The mask is authorized for distribution under FDA enforcement discretion during the COVID-19 outbreak unless the authorization is terminated or revoked sooner

DO NOT USE FOR

Procedure mask is not a respirator and is not designed to replace N95
 This mask is not for a place where the infection risk level through inhalation exposure is high

TIME USE LIMITATION

Replace the mask when it becomes dirty, damaged, or difficult to breathe through

TESTING AND STANDARDS

ASTM F2100 Level 3 (Report from Nelson Lab)

| TEST | YY-0469 | EN 14683 Type IIR | ASTM F2100 Level 3 | Typical Value |
|--|--------------------------------|--------------------------------|--------------------------------|------------------------------|
| Bacterial Filtration Efficiency, % | ≥95 | ≥98 | ≥98 | 99 |
| Differential Pressure, mm H ₂ O/cm ² | < 5.0 (49 Pa/cm ²) | < 6.1 (60 Pa/cm ²) | < 6.0 (59 Pa/cm ²) | 4.2 (41 Pa/cm ²) |
| Particulate Filtration Efficiency 0.1 Micron, % | ≥30 | Not Required | ≥98 | 99 |
| Synthetic Blood Resistance mmHg | 120 (16.0 kPa) | 120 (16.0 kPa) | 160 (21.3 kPa) | 160 (21.3 kPa) |
| Flame Resistance | Burn < 5s | Not Required | Class 1 | Pass |

SHELF LIFE AND STORAGE

2 years from the date of manufacture
 Use by date on box in MM/YYYY format
 Store masks in the original packaging, away from contaminated areas, dust, sunlight, extreme temperatures, excessive moisture, and damaging chemicals
 Store in temperatures between -4°F (-20°C) and +86°F (+30°C) and not exceeding 80% humidity

WARNINGS ⚠

The masks are not intended for reuse and shall be discarded after each procedure.
 Check the production date. Masks expire two years after the production date, after which they may not provide full protection. Before use, the wearer must read and understand the user instructions provided in the product packaging. Not recommended for children under 3.

ORDERING INFORMATION

| DESCRIPTION | Case Size | Case Weight | Masks/Box | Boxes/Case | Masks/Case |
|----------------|--------------|-------------|-----------|------------|------------|
| Procedure Mask | 52*37.5*36cm | 9.0KG | 50 | 40 | 2000 |